

AC - P509R LUXURY FLOOR TYPE



SPECIFICATIONS

1. TYPE : AC-P509R LUXURY FLOOR TYPE-(AIR INPUT FROM CENTRAL, CLEAN AIR OUT FROM TOP)
2. VOLTAGE/ WATTAGE : AC110V / 220V 60HZ / 66W
3. AIR FLOW : HIGH 450CFM / MID.345CFM / LOW185CFM
4. MOTOR TEMPERATURE : HIGH 51.5°C / MID 44.8°C / LOW 43.4°C
AUTO CUT MOTOR PROTECTOR :125°C
5. SPEED CONTROL : WIRELESS CONTROLLER-4 STAGES
AUTO/HI/MED/LOW(TIMER SHUTDOWN / BOOKING 1.2.4.8HR)
AUTO SENSOR MONITOR: VOC CHEMICAL SUBSTANCE/SMOKE AUTO SENSOR MONITOR.
WHEN BAD AIR QUALITY OR HIGH CONCENTRATION VOC, IT WILL AUTO START TO H
SPEED(H:RED; M :ORANGE; L: GREEN LIGHT)

SPECIFICATIONS

- 6. NOISE RATINGS(DB) : HIGH / 50DB MID. / 46DB LOW / 40DB
- 7. DIMENSIONS SURFACE SIZE : HEIGHT 858 × W432 × T342 MM
- 8. INDICATOR LIGHT : STAGE OPERATE / HIGH VOLTAGE INDICATOR / TIMER INDICATOR
- 9. TURBINE MOTOR / 1 SET HIGH FUNCTION, LOW NOISE , STRONG WIND, LARGE SUCTION, TWO LAYERS METAL FAN PLEATED: TURBINE FAN
- 10. AIR INPUT / OUTPUT DESIGN : AIR SUPPLY FROM CENTRAL OF MACHINE, AND SENT OUT THE CLEAN AIR FROM TOP, DIRECT WIND MOVING, / INDEPENDENT PLATE ON TOP , 360 DEGREE 3D CIRCULATE, FAR WIND BLOW, HIGH EFFICIENCY.
- 11. CELL VOLTAGE (TWO STAGE) : IONIZING SECTION: 8,000VDC COLLECTION SECTION: 4,000VDC
- 12. COLLECTING BOXES / PITCH : 71 PCS / 4MM
- 13. COLLECT EFFICIENCY : 0.3μM—7μM 98.7% CERTIFICATION BY INDUSTRIAL TECHNOLOGY RESEARCH INNOVATION TAIWAN F55RD1D00-070
- 14. WEIGHT : 26KG
- 15. SUITABLE SQUARE METER : WITHIN 70 SQUARE METER (DEPENDING ON POLLUTION SITUATION)
- 16. ACCESSORY WITH MACHINE : WIRELESS CONTROL、CARBON FILTER、TECHNICIAN BROCHURE
- 17. OPTIONS : UV LIGHT / TIO₂ / ION / SPECIAL FUNCTION FILTERS